

The Leading Manufacturer of Vertical Form Fill and Seal Packaging Solutions

**GIC3000** 





The GIC3000 is a high-speed continuous motion servo machine ideal for producing a wide range of pack formats with bag widths of up to 250mm. The GIC3000 incorporates robust proven mechanical design and the latest Allen Bradley maintenance-free servo technology to ensure industry leading reliability and low cost of ownership.

# **Applications**

The GIC3000 is suitable for a wide range of applications including (but not limited to);- Fresh and frozen foods, snacks and confectionery, powders and pulses, salad, herbs and protein.

## **Integration**

The GIC3000 is designed to integrate with all types of infeed feed systems; including, multi-head weighers (MHW), augers, linear weighers, volumetric pumps, counters and cup fillers. Downstream plant interface connections are also provided.

#### **Pack Styles**







**Pillow** 

Quad

Punch Hole





Euroslot Zip

### **GIC3000**

**MAXIMUM FINISHED FLAT BAG WIDTH: 250mm** 

**MAXIMUM SPEED:** 115 PACKS PER MINUTE

POWER SUPPLY: 3 PHASE SUPPLY - 415V 3PH + N AND E. 25A PER PHASE D RATED

**COMPRESSED AIR REQUIREMENT: DEPENDENT ON SPEED AND APPLICATION** 


FINISH: BLACK HARD ANODISED ALUMINIUM AND STAINLESS STEEL


PACKAGING MATERIALS: ALL SUITABLE HEAT SEALABLE MATERIALS INCLUDING LAMINATES AND POLYETHELENES (OPTIONAL IMPULSE SEALING). CAN BE ADAPTED FOR PAPER

**REEL OUTER DIAMETER: 450mm** 

**REEL CORE DIAMETER: 76mm** 

WEIGHT: 1100kg





### **GIC3000 Machine Specification**

- Full maintenance-free Allen Bradley Kinetix 5500 Servo Drives
- Allen Bradley Compact Logix PLC
- Full feature 10-inch colour Allen Bradley panel view plus 7 1000 MMI touch screen
- Servo driven twin belt film transport with vacuum assist
- Rotary band back seal system fitted as standard
- Wrapper print registration (PEC)
- Reel run out sensor
- · Low level cantilevered film feed air mandrel, allows for easy loading of film reels
- Full SMC pneumatics with additional manifold capacity built-in
- Pneumatic mechanical web tension control with electronic monitored actuation
- Manual film tracking incorporating coder and labeller
- Pack discharge chute
- Provision for integrated Coder mounting and print roller
- Manual splice table with integrated tape dispenser
- PETG safety guards (10mm thick) complete with safety switches

#### **Optional Features**

- Remote access
- Full stainless steel and high care upgrade
- Gas flushing
- Impulse poly-welding and alternative sealing systems
- Label application and print options
- Discharge elevator
- Pack turning device
- Bag shaker
- Deflator unit
- Carry bag handle application
- Static eliminator













